Name	Category	Description	Variant 1 - Name	Variant 1 - Price	Variant 1 - SKU	Variant 2 - Name	Variant 2 - Price	Variant 2 - SKU	Variant 3 - Name	Variant 3 - Price	Variant 3 - SKU	Variant 4 - Name	Variant 4 - Price	Variant 4 - SKU	Variant 5 - Name	Variant 5 - Price	Variant 5 - SKU	Variant 6 - Name	Variant 6 - Price	Variant 6 - SKU	Variant 7 - Name	Variant 7 - Price	Variant 7 - SKU	Variant 8 - Name	Variant 8 - SKU
10 Amp Switched Power Socket Adapter	Accessories	10 Amp fused power socket adapter with integrated switch. Terminates to tinned bare ends Not all extensions are created equal. We custom make our barrel extensions for you. Molded plugs for rugged strain relief Round jacket for added conductor protection Pure stranded copper 18 AWG wire for full connector current rating	Regular	$20.00	10A.PSA																					
2.1 x 5.5 Barrel Extension	Accessories	2.1 x 5.5 connectors 2.1 x 5.5 mm barrel to bare wire leads. 18 AWG cable 6" length The wires are color coded to indicate barrel size. Black: Negative (Cathode) White: Positive (Anode)	6 foot extension	$5.00	2.1x5.5.6	12 foot extension	$6.00	2.1x5.5.12																	
2.1 x 5.5 Barrel to Bare Wire Adapter	Accessories	Not all extensions are created equal. We custom make our barrel extensions for you. Molded plugs for rugged strain relief Round jacket for added conductor protection Pure stranded copper 16 AWG wire for full connector current rating 2.5 x 5.5 barrel connectors	Power input	$2.00	2.1x5.5.M	Power output	$2.00	2.1x5.5.F																	
2.5 x 5.5 Barrel Extension	Accessories	2.5 x 5.5 mm barrel to bare wire leads. 16 AWG cable 6" length The wires are color coded to indicate barrel size. Black: Negative (Cathode)	6 foot extension	$6.00	2.5x5.5.6	12 foot extension	$7.00	2.5x5.5.12																	
2.5 x 5.5 Barrel to Bare Wire Adapter	Accessories	Red: Positive (Anode) The wires are color coded to indicate barrel size. 35 Amp rated locking DC connector	Power input lead	$2.50	2.5x5.5.M	Power output lead	$2.50	2.5x5.5.F																	
35 Amp 4 Wire Connector	Accessories	One male and one female connector included	Male	$10.00	CUSHCONN.35A.M	Female	$10.00	CUSHCONN.35A.F	Male Panel	$9.00	CUSHCONN.35A.M.P														
9V Battery Adapter	Accessories	Adopt a 9 volt battery to a 2.1mm DC jack Locking solder-less push-in mechanical connectors. *According to NEC 2008 max. current ampacity based on conductor size.	Regular	$1.00	9v.ADP																					
CQK	Accessories	Highest Current Capacity: max 20 A Input max 6 A Output	CQK 2	$2.00	CQK2	CQK 3	$2.50	CQK3																	
Cinema White Extension	Accessories		By the foot	$0.90																					
Edison to IEC Adapter	Accessories	6' Edison male to IEC female adapter Phoenix connectors for all of our controllers.	Regular	$8.00	IEC.ADAPT																				
Phoenix Connectors	Accessories	PH6- 4x4 DMX controllers PH4- 24 channel Power output PH2.20.I- CDT Power Input PH2.15.O- CDT Power Output PH3.15.M Cinema White Male Ph3.15.F Cinema White Female PH4-.15.M RGB Male Connector PH4.15.F RGB Female Connector One male and one female Screw set DC jack. Available sizes:	CDT Power Input 20 Amp	$2.99	PH2.20.I	CDT Power Ouput 15 Amp	$2.99	PH2.15.O	Cinema White Male Connector	$2.99	PH3.15.M	Cinema White Female Connector	$2.99	PH3.15.F	RGB Male Connector	$3.99	PH4.15.M	RGB Female Connector	$3.99	PH4.15.F	4X4 DMX Controller Connector	$5.00	PH6.I		
Phoenix to Barrel Adapter	Accessories	2.1mm x 5.5mm 2.5mm x 5.5mm	2.1 Set	$3.00	PH2.1.MF	2.5 Set	$3.50	PH2.5.MF	2.1 Male	$1.50	PH2.1.M	2.1 Female	$1.50	PH2.1.F	2.5 Male	$1.75	PH2.5.M	2.5 Female	$1.75	PH2.5.F					
Portable Power Cable	Accessories	Professional grade flexible cords are UL and CSA listed for continuous submersion in water. Jacket is heat, moisture, and oil resistant. Jacket is sunlight resistant SOOW Rated up to 600-Volts SJOOW Rated up to 300-Volts 2,3,4 or 5 Flexible stranded class K copper conductors Price is per foot	14.4.SJO	$1.25	14.4.SJO	14.5.SOOW	$1.50	14.5.SOOW	14.6.SOOW	$1.80	14.6.SOOW														
Power Gauge	Accessories	With our Power gauge you are in control. Accurately measure with the following precision: Current 0-150 Amps, 0.01A accuracy Voltage 0-60 Volts, 0.01V accuracy Watts 0-6554 Watts, 0.1W accuracy Average current 0-65 Amp hours, 0.001 AH accuracy Watt Hours 0-6554 Watt hours, 0.1 WH accuracy Display is back lit for easy reading in all lighting situations.	150 Amp Power Gauge	$35.00	150.GAUGE																					
RGB Flat Extension Wire	Accessories	Not all wire is created equal. We custom make our wire assemblies for you. 18 gauge Copper four wire flat conductors. This is not a cheap aluminum or copper clad product. Clear outer jacket for additional conductor protection Color coded for easy identification Solder less "Quick-On" styler connector for our 12mm RGB ribbon.	By the foot	$0.90	18.4.flat	328 foot spool (100 meters)	$262.40	18.4.flat.100																	
RGB Quick Connector	Accessories	This connector is available with or without wire and helps when creating corners. Four wire RGB extension with locking connectors Rated for 300 diodes.	Style 1 RGB Union for 12mm ribbon	$2.00	12.RGB.UNION	Style 2 RGB Quick on to bare wire for 12mm ribbon	$2.00	12.RGB.Q.O	Style 3 RGB Quick on Jumper for 12mm ribbon	$2.00	12.RGB.JUMP	Style 1 RGB Union for 10mm ribbon	$2.00	10.RGB.UNION	Style 2 RGB Quick on to bare wire for 10mm ribbon	$2.00	10.RGB.Q.O								
RGB Tail Extension	Accessories	1 male and 1 female	39" RGB Tail Extension	$10.00	EXT.RGB	6" RGB Tail	$5.00	TAIL.RGB																	
XLR Connector	Accessories		3 Pin XLR Male	$3.00	XLR3.M	3 pin XLR Female	$3.00	XLR3.F																	
XLR Connectors	Accessories		XLR 3pin Male	$3.00	XLR.3.M	XLR 3pin Female	$3.00	XLR.3.F																	
Cinema White	Color Corrected Diodes	UL Listed Featuring our Color Corrected Diodes Variable White LED Tape. CRI >95 (5 meter) spool 10mm Copper Dense Printed Circuit Board 12v DC 600 diodes 300 Tungsten, 300 Daylight diodes Included accessories o (1) quick connect union o (1) quick connect power lead UL Listed Color Corrected Daylight LED Tape.	Cinema White	$240.00	CW.600	IP65	$260.00	CW.600.IP65																	
Color Corrected Daylight LED Tape	Color Corrected Diodes	CRI >95 1696™ 49K (5 meter) spool 10mm White Printed Circuit Board 12v DC 600 diodes 1 male and 1 female Cush Light 2.1 x 5.5 18 AWG leads attached Included accessories o (1) quick connect union o (1) quick connect power lead UL Listed High Rendering Tungsten LED Tape.	IP20	$240.00	CCD.55.600.20	IP65	$260.00	CCD.55.600.65																	
Color Corrected Tungsten LED Tape	Color Corrected Diodes	CRI 95 (5 meter) spool 10mm Copper Printed Circuit Board 12v DC 600 diodes 1 male and 1 female Cush Light 2.1 x 5.5 18 AWG leads attached Included accessories o (1) quick connect union o (1) quick connect power lead	IP20	$240.00	CCD.32.600.20	IP65	$260.00	CCD.32.600.65																	
Cush Flex	Color Corrected Diodes	The most versatile tool in your lighting kit is here. With parallel circuitry Cush Flex sheets can be cut to fit your your needs. They can be powered via 12 volt DC anywhere you see copper. From on the table up lighting to in the corner cove lighting. Being flexible means being free. Free to put light where you need it, Need us to finish it for you. Add a flex backer kit to your cart and we will add velcro for affixing accessories, grommets for hanging and a custom tail of your choice. Phoenix 3 pole Cinema White connector or CQK3 locking connectors. Cush.Flex.744 120 Watts of LED illuminance 744 Color Corrected Diodes 372 Tungsten CCD 372 Daylight CCD Cut segment width: 5/8" Cut segment Length: 2-3/8" Total sheet dimension 9-1/2" x 20" Cut points every 6 LEDs (cut group) 4 cut groups per line, total 31 lines. DC12V White PCB High temperature 3m Adhesive backed Cush.Flex.600 100 Watts of LED illuminance 600 Color Corrected Diodes 300 Tungsten CCD 300 Daylight CCD Cut segment width: 3/4" Cut segment Length: 2-3/8" Total sheet dimension 9-1/2" x 20" 4 cut groups per line, total 31 lines. DC12V White PCB High temperature 3m Adhesive backed Cinema White Rigid is the piece you have been waiting for...	Cush Flex 600 Sheet	$300.00	Cush.Flex.600	Cush Flex 744 Sheet	$350.00	Cush.Flex.744	Flex backer kit	$75.00	Flex.Backer.kit														
Rigid Cinema White	Color Corrected Diodes	Flexible along the length yet Rigid enough to hang Pre punched for easy mechanical fastening Cuttable Every 6 diodes with Copper dense circuits (4") Solder-less connection terminals at both ends Color Corrected Variable White Diodes (CRI >95) Sold in 1 Meter Lengths (39") 120 diodes (60 Tungsten, 60 Daylight) 12v DC	Per Meter	$50.00	RIGID.Cinema																					

Leviton 3000 Series Controller — DMX Controllers

Save money and time with this easy to use controller.
Controls are intuitive and practical for easy effects gags.

FEATURES
DMX512 output
4 or 8 dimming control channels
4 or 8 recordable scene memory
Chaser functions:
- (2) selectable chases
- Channel chase
- Scene chase
- Speed control
- Direction control
- Audio input
Bump buttons for each channel or scene
Master output fader

SPECIFICATIONS
Power Supply: +100 â€“ 240VAC â€“wall wartâ€
Control Signal: DMX512-A
Connector: 3-pin or 5-pin female XLR
Audio Input: Maximum input -10 db 100mV
Dimensions (W x H x D): 9.13 in (232 mm) x 6.70 in
(170 mm) x 2.20 in (56 mm)
Weight: 2.4 lbs (1.2 kg)
Shipping Weight: N3004 3.0 lbs (1.5 kg),
N3008 3.36 lbs (1.18 kg)
[6] Sub-masters & (1) Master Fader
[40] Scene Memory
Scene Memories can be assigned to Sub-Masters
Access to all (512) DMX control channels from keypad
Backup Console Mode â€“ Scene fade and activation
upon sudden loss of incoming DMX signal
Simple to use and easy to carry
Silver finish
Operates from included re-chargeable battery or from
included power supply
Supports DMX Snapshot
LCD Power Save mode

Option	Price	Option	Price
8 Channel	$265.00 N3008-D	4 channel	$200.00 N3004-D

Leviton mini DMX Console — DMX Controllers

SPECIFICATIONS
Console Power: 12V/1A DC
Included Wall Wart: 120-260VAC
DMX Input: (1) Male 5-Pin XLR, DMX output,
conforms to DMX512-A
DMX Output: (1) Female 5-Pin XLR, DMX output,
conforms to DMX512-A
DMX Signal Connection: XLR 5-Pin
Battery Type: 1.2V NiMH AA rechargeable battery pack
Battery Charge Time: 5 hours
3 hour operating time from battery
Dimensions (L x W x H): 10.31 in (262 mm) x 5.20 in
(132 mm) x 1.77 in (45 mm)
Weight: 4 lbs (2 kg)
Live Show Tested and Approved

Option	Price
Mini DMX console	$325.00 N1000-6

Wireless DMX system — DMX Controllers

This economical wireless dmx system will free you from wires and make those moving set pieces a snap. Each unit can operate as a transmitter or a receiver. They can be powered via battery or a switching power supply adapter included with your purchase

Specifications:
2.4G DMX512 wireless receiver/transmitter
2X8 bit LCD display
16 group modes for multiple universes in the same location
Input voltage: 9-12VDC 300MA MIN
Communication distance: 400M(visible distance)
Working frequency: 2.4G ISM, 126 channels
Max transmitting power rate: 20dBm
Receive sensitive: -94dBm
DMX single terminal: 3PIN male-female socket
Dimension: 2.95x1.79x1.69 inches (75X147X43 mm)
Net weight: 360g

Option	Price	Option	Price
1x Transceiver	$150.00 WDMX.X1	3x Transceiver	$425.00 W.DMX.X3

CDT 4.10 — LED Dimmers

Simplicity... Our CDT.4.10 dimmers are a great addition to your LED solution. With a massive 10 amps per channel and four channels they are ready to control your largest of fixtures. Whether you need two Cinema White groups, One RGB fixture or an RGBW fixture. They can be controlled locally via up and down buttons on the display cycling between channels with the Mode button. Press the mode button again to set the address for DMX mode.

Dmx connection can be made via 5 pin XLR or RJ45
Multiple Tap Power input terminals allow for smaller gauge wire and the use of multiple smaller power supplies.

4 Channel x 10 Amps per channel
480 Watts @ 12 volts
960 Watts @ 24 volts
Welcome to our DMX only line of Cinematic dimming technology. These controllers are small in size but big in features:

Option	Price
CDT.4.10	$180.00 CDT.4.10

CDT DMX only — LED Dimmers

8/16 bit dimming modes
DMX Signal Isolation
DMX Signal Amplifier
DMX Terminator
Adjustable PWM frequency: This can be helpful in reducing the switching load on your power supply.
Dmx connection can be made via 5 pin XLR, RJ45, or screw terminals.
Multiple Tap Power input terminals allow for smaller gauge wire and the use of multiple smaller power supplies.

CDT.8.10
8 Channels at 10 amps per channel
960 Watts @12 Volts
1920 Watts @ 24 volts

CDT.12.7
12 Channels at 7 amps per channel
1008 Watts @ 12 volts DC
2016 Watts @ 24 volts DC

Option	Price	Option	Price
CDT.8.10	$200.00 CDT.8.10	CDT.12.7	$225.00 CD.12.7

24 Channel DMX Controller — LED Dimmers

24 channel DMX Controller.
3 Amps per channel output.
Designed Architectural Lighting Applications

Option	Price
Regular	$277.00 DMX.24.3.22kh

4 Channel DMX Controller Television Safe — LED Dimmers

This controller has been custom programmed to our standards
They are used regularly in Live broadcast television shows shooting at standard frame rates.Input 12/24v DC 192 Watts
Output 4 channels @ 4 amps Max per channel Dip Switch address setting
Function setting for preset effects and channel output selection
3 pin XLR DMX connectors in/out RJ45 DMX connectors in/out
This is our flag ship LED controller. It offers local control, dmx control, and a built in effects engine. All the features you could want have been packed into this one powerful device.

Option	Price
4x4	$75.00 DMX.4.4

CDT 3.7 — LED Dimmers

Motion picture grade Cinematic Dimming Technology
12-24 Volts DC inputThree channels rated at 7 amps continuous current
15 Amps total continuous maximum output current
Dmx control via rj45 or 5pin XLR
4 DMX modes 3, 7, 14, 28 channel
Local Static Control over three independent channels
Numeric Display
Built in Effects Generator
Feature lock, prevents accidental adjustment of values
Short circuit protection
Over current protection
Film Grade LED Drivers.
Short Circuit Protection
Silent Operation
Sealed for optimal performance in harsh conditions

Option	Price
CDT.3.7	$450.00 CDT.3.7.15

AC /DC LED Driver — LED Drivers

Option	Price	Code
24 Watt	$20.00	
12.24 60 Watt	$50.00	12.6
102 Watt	$85.00	12.102
120 Watt	$100.00	12.12
150 Watt	$125.00	12.15
192 Watt	$160.00	12.192
192 Watt IP65	$175.00	12.192.65
600 Watt IP65	$400.00	12.600.65

Lithium Driver — LED Drivers

12 Volt 22 Amp/Hour
Lithium Ion LED Driver
Short circuit protection
Built in Charging regulator
On board battery percentage indicator
Dual mode low battery warning
Charges with any 12 volt source

Option	Price
22 Amp Lithium Driver	$450.00 22.12.Li

NiMH Charger — LED Drivers

This is our three channels Universal Fast and Smart Charger. Each channel can charge any 9.6-18.0V NiMH and NiCd battery pack
3 x 5.5x2.1mm Female Barrel Jack per channel.
The package include the following items:
1 x 3 channels charger
1 x AC power cord
3 x 5.5 x 2.1mm barrel male to standard tamiya female connector adapter.
3 x Standard Male Tamiya connector to standard Mini Female connector connector adapter
3 x standard male Tamiya connector clip adapter.
Dimension: 1.8" (46mm) H X 5.8" (147mm) W X 6.8" (250mm)L.
Weight: 27oz / 765g

Option	Price
3 port 1.8 Mah Charger	$155.00 3xNiMH

NiMH Rechargeable Battery, 12V DC, (5s2xAA) 2.2 Ah, FP.
This pack provides 12V DC and has a 4A MAX LOAD
It is safety-protected with a 4.0A polyswitch and features a 2.1 mm x 5.5 mm female barrel connector.
It weighs 9.8 oz (280 g) and is 4.1" x 3.0" x 0.7" (LxWxH).
The charging time is about 2.5 hrs when charged using the 0.9A charge setting.

4.5 Amp Hour 12 Volt FP
NiMH Rechargeable Battery, 12V DC, (5s2xAH) 4.5 Ah, FP.
This pack provides 12V DC and has a 4.5A MAX LOAD.
It is safety-protected with a 4.5A polyswitch and features a 2.1 mm x 5.5 mm female barrel connector.
It weighs 1.0 lbs, 7.6 oz (670 g) and is 5.4" x 3.6" x 0.8" (LxWxH).
The charging time is about 3.0 hrs when charged using the 1.8A charge setting.

10 Amp Hour 12 Volt FP
NiMH Rechargeable Battery, 12V DC, (5s2xD) 10 Ah, FP
This pack provides 12V DC and has a 7A MAX LOAD
It is safety-protected with a 7.0A polyswitch and features a 2.1 mm x 5.5 mm female barrel connector.
It weighs 3.0 lbs, 11.2 oz (1680 g) and is 5.5" x 3.5" x 0.75" (LxWxH).
The charging time is about 6.6 hrs when charged using the 1.8A charge setting.

Notes:
Do not discharge the battery pack below 10V, as this may damage the NiMH battery pack.
Charging the battery immediately after use is recommended.
Charge with 900/1800 mA charger.
12-24 volt dc input
Up to 4 amps/ channel

Product	Category																
NiMH Driver	LED Drivers	2.2 Amp Hour 12 Volt FP	$75.00 2.2AH.12v.NiMH	4.5 Amp Hour 12 Volt FP	$140.00 4.5AH.12v.NiMH	10 Amp Hour 12 Volt FP	$200.00 10AH.12v.NiMH										
Rgb Amplifier	LED Drivers	Regular Price	$15.00 RGB.AMP														

Powered by 2.1 x 5.5 dc plug
Three DMX512 Universes (1536 channels) combined into one CAT-5 cable.
RJ45 connectors used for connection with inexpensive CAT-5 cables.
Gold-plated pins on RJ45 connectors.
Sturdy molded housing.
Mountable on DIN rail.
Mountable in lighting-rig.
Use as flexible DMX outlet.
Mountable with 5mm/0.28€ screws or cable-tie.
Weight including packaging, 67g/2.36oz.
Easy to use.
Low cost.

| Compander | Networking | Regular Price | $18.00 DMK.COMP |

Data.Ext
RJ45 snag-less extension
Constructed with 4-pair 26 AWG bare copper stranded wire
UL listed and CMG / FT4 fire rated jacket.
These cables are constructed with the Ultra Slim Low Profile boot, protecting the tab without any additional width to the plug

| Data Ext | Networking | 1' | $2.00 Data.Ext.1 | 3' | $3.25 Data.Ext.3 | 7' | $5.00 Data.Ect.7 | 14' | $8.50 Data.Ext.14 | 30' | $10.00 Data.Ext.10 | 25' | $15.00 Data.Ext.25 | 50' | $20.00 Data.Ext.50 | 100' | $40.00 Data.Ext.100 |
| RJ45 Terminator | Networking | Regular | $3.00 RJ45.TERM |

Eliminate feedback issues in your DMX system with this simple solution from Martin.
Adapt cost effective Cat5 extensions into your existing DMX System.

XLR/45 Facts & Features:

Use an ordinary CAT-5 ethernet cable to make a DMX512 cable together with two XLR/45 adapters.
Plug the XLR/45 directly into any 3 or 5-pin XLR DMX512-controlled equipment.
Four XLR/45 versions available, male or female 3-pin or 5-pin XLR to RJ45.
Combine different adapters as needed.
Very robust, rugged molded housing with non-slip grip.
Gold plated pins on connectors.
Sturdy shell style packaging.

| XLR/45 | Networking | http://www.cpoint-lighting.com/products/product_xlrj45/index.htm | RJ45 to 5 Pin XLR Male | $15.00 XLRJ.5M | RJ45 to 5 Pin XLR Female | $15.00 XLRJ.5F | RJ45 to 3 Pin XLR Male | $15.00 XLRJ.3M | RJ45 to 3 Pin XLR Female | $15.00 XLRJ.3F |

UL Listed
Python RGB LED Strip
Theatrical color mixing
16'4" (5 meter) spool
12mm White Printed Circuit Board
12v DC
150 diodes
Included accessories
o (1) make 4-pin locking connector
o (1) female 4-pin locking connector
o (1) quick connect union

| RGB Python 150 | Theatrical RGB LED Tape | Python 150 | $100.00 RGBW |

UL Listed
High Output Python RGB LED Strip
Theatrical color mixing
16'4" (5 meter) spool
12mm White Printed Circuit Board
12v DC
72 Watts
300 diodes
Included accessories
o (1) male 4-pin locking connector
o (1) female 4-pin locking connector
o (1) quick connect power lead

| RGB Python 300 | Theatrical RGB LED Tape | Python 300 | $180.00 RGBWHO |

UL Listed
High Output Viper RGB LED Strip
Theatrical color mixing
16'4" (5 meter) spool
12mm Black Printed Circuit Board
12v DC
300 diodes
Included accessories
o (1) male 4-pin locking connector
o (1) female 4-pin locking connector
o (1) quick connect union
o (1) quick connect power lead

| RGB Viper 300 | Theatrical RGB LED Tape | Viper 300 | $180.00 RGBBHD |
| Shop Labor Per Hour | | | $100.00 SHOP.LABOR |